# A MODULAR APPROACH TO ELECTRONIC FUZE DEVELOPMENT

#### MIKE TUCKER





#### PRESENTATION CONTENTS

- Company Background
- International Fuzing Trends
- Customized Fuze Features
- Risk Areas in Artillery Fuze Development
- Development Approach
- Fuze Components
  - Customized Features
- Derived Range of Fuzes
- Future Possibilities
- Summary
- Conclusion






#### **FUCHS ELECTRONICS - BACKGROUND**

- Privately owned South African Company
- Designs and Manufactures <u>Electronic Fuzes</u> for Tube-Launched Ammunition
  - Artillery Fuzes
  - Rocket fuzes
  - Naval Fuzes
  - Mortar Fuzes
  - Fuze Setting Systems
- Staff of Approx. 280
- Supplies Internationally to Ammunition Suppliers and end-users
- Almost 100% of Production is Exported





## FUZE PRODUCTION PERCENTAGES BY PRODUCT TYPE \*



\* Based on sales of past 20 Years



## International Artillery Fuzing Trends

- Customer Requirements:
  - Short Timescales Typically 4 to 6 months to Production
  - Reduced Production Volumes
  - Customized Features
  - Proven Safety, Reliability and Qualification Status
  - Very High Probability of Project Success





#### Customized Fuze Features

- Safety Times
- Burst Heights
- PD Backup feature and its Arming time
- Multi Role Usage e.g. Proximity, Time, PD, PD Delay
  - With or Without Delay Function
  - Post Impact Delay Time
- Function Switch
- Inductive Settable Features
- On-Board Displays of e.g. Time Set
- Delivery Timescales are always shorter than needed for a full development cycle!







## Risk Areas in Artillery Fuze Development

- Component breakage due to launch stresses at Highest Charges
- Survival of in-flight temperatures and pressures
- Trajectory Bursts due to:
  - Noise effects
  - Vibration
  - Ammunition instability
- Compatibility with Rocket Assisted or Base bleed Ammunition
- High Cost of Dynamic Proofing
- Lead times of Electronic components





## Development Approach

- To satisfy the requirements, the following approach has been adopted successfully:
  - Use Integrated Development Teams within the company:
    - Electronics Engineers
    - Mechanical Engineers
    - Pre-Production Representatives
    - Instrumentation Development Enginers
    - Quality Control Engineers






### Development Approach - II

- Use of proven "Building Blocks"
- In-house Prototype Manufacturing Department
- Regular Dynamic Proofing
  - Use of In-Flight Telemetry
  - Easy access to well instrumented Proof Ranges
- Development of Dedicated Test Instrumentation

```
Sync. No. 7989 L9
Fuze No. 0065535
Mode: PX Hi 200.0
Count Down: 1085
Volts=27.2 SFM04
Delta=05 Gain=00
```



## Typical electronic fuze components



Rf antenna

**Inductive setting coil** 

**Processing electronics** 

**Reserve battery** 

Switch


Firing circuitry

**Detonator** 

Safe and arm device/ booster







Rf antenna for Prox / Telemetry

**Inductive setting coil** 

**Impact sensor** 

**Processing electronics** 

**Interconnection harness** 



## Electronic Head Assembly

#### STANDARD FEATURES:

- Microprocessor Controlled
  - Software programmed during final assembly
- Inductively Settable or Factory Set Only
- DATA stored in EEProm
  - Re-Writeable via Inductive coil interface
  - Mission Settings, e.g. Proximity with 6.5 sec Safety time






## **Electronic Head Assembly**

- CUSTOM FEATURES
  - Proximity / Time / PD Functions
    - Safety Time for PD Backup
    - Proximity Enable / Safety Time
    - Proximity Algorithm
    - Burst Heights
  - Switch Setting
  - Production / Engineering Settings
    - RF Transmission Characteristics
    - Signal Processor Characteristics
    - Telemetry Features












## Lower Module Assembly

#### • FEATURES:

- Fire circuitry
- Power supply circuitry
- Detonator interface
- Interface to switches or displays

#### CUSTOM FEATURES

- Fire circuit safety times
- Post impact delay time







## General construction



Nose cone

**Fuze body** 

**Push buttons** 

**Display** 

Safe and arm device



**Display** 



**Mode switch** 



#### **General Construction**

- FEATURES:
  - Houses all sub-assemblies
- CUSTOM FEATURES
  - Switches for MOFA or PROX/PD
  - Buttons for time fuze setting
  - Display for time fuze setting
  - Safe and arm device
    - 40m or 200m Options







SAFE AND ARM DEVICES



## Derived Range of Artillery Fuzes



ARTILLERY PROXIMITY,
ELECTRONIC PD / DELAY
AND MOFA FUZES



**FUZE SETTER** 



**ARTILLERY TIME FUZES** 



#### **Future Possibilities**

- Further Enhance Flexibility by:
- Mid Life Software Upgrade to Fuzing Systems
  - Depot Modification of Microprocessor code via Inductive Setting Coil
  - (Currently done by hard wiring at final production stage)
- Examples:
  - Convert Proximity Fuzes to Multi-Role Fuzes
  - Upgrade ECCM features as a software retrofit
  - Improve reliability by use of improved signal processing





## Summary

- Benefits of a modular development approach:
  - Significantly reduced number of Dynamic Firings
  - Reduced Development Time
  - Reduced Technical Risk
  - Increased Manufacturing Flexibility
    - Different Fuzes can be produced with the same material
  - Reduced Life cycle cost
    - Software only Mid-life upgrades
  - Re-work or Re-use of fuzes without physical disassembly





#### **CONCLUSION**

A modular approach to electronic fuze development assists in reducing 'time to market' and development costs as well as reducing risks involved in adopting untested hardware



